

Commercial Tapware



GUARDIAN[®] TAPWARE



Bench Mount Infrared Sensor Tap

T-3MSS-HMSTB


T-3MSS-HMSTB-TV

T-3MSS-HMSTM

T-3MSS-HMSTM-TV

Available in mains or battery powered, with optional tempering valve

- Battery Powered – 2x CR123 3V Lithium Batteries Estimates 80,000 Cycles
- Mains Powered – 6V Transformer
- Full S/S Construction
- Sensor Range Nominal: 50mm – 200mm
- Maximum Run Time: 60 Seconds
- WELS 6 Star 4LPM
- Working Pressure Range 150kPa-500kPa
- Maximum Operating Temperature 50 Degrees



Battery holder
T-3MSSP-HMST-BP
(in control box)

2x CR123 3V
Lithium Batteries



240v power adaptor
T-3MSSP-HMST-M
(Std 800 mm power cord)

T-3MSSP-HMST-3M
(with 3m power cord)



1/2" MI BSP inlet

Solenoid control box
T-3MSSP-HMST-CBS


Outlet to tap
1/2" MI BSP

Top

Front



Side



T-3MSSP-HMST-M



T-3MSSP-HMST-CBS



T-3MSSP-HMST-BP

Flexible inlet hose to solenoid unit
nom length 350mm
1/2" FI BSP

Power and control leads



T-3MSSP-HMST-3M

* Power Supply with 3 metre lead available separately

*Exclusions apply

3monkeez.com.au